

## POWERBAR - PXC5PHTTS-TS04-B

### C-PDU [4] TIS outlet, Surge Protection, Illuminated Master Switch & Overload Protection with LED power indicator, TIS 16A Plug, Cable 3m with 1.5 sq.mm.

#### Electrical

|                            |                                           |
|----------------------------|-------------------------------------------|
| Input connector            | 1 x TIS166 16 A plug                      |
| Output connectors          | 4 x TIS166 outlets with eyes shutter      |
| Nominal input voltage      | 200~250 VAC                               |
| No. of phases              | 1 phase                                   |
| Acceptable input voltage   | ± 10% of normal voltage                   |
| Input frequency            | 50/60 Hz                                  |
| Max. Power                 | 3,680 W                                   |
| Length of connection cable | 3m x IEC53 60227 (comply with TIS11/2553) |

#### Physical

|                                 |                                                                                 |
|---------------------------------|---------------------------------------------------------------------------------|
| Power Input                     | Left end single input                                                           |
| Bracket Installation            | Interchangeable L mounting brackets (4 directions)                              |
| Rack Installation               | Vertical Mounting in Rack 19"                                                   |
| Control Function                | Illuminated Master Switch with Plastic cover                                    |
| Protection Function             | Built-in Surge Protection 10kA 350Joule & Overload protector 16A with indicator |
| Case Material                   | Aluminum Alloy (black)                                                          |
| Outlets Material                | PC-ABS (black)                                                                  |
| Insulation                      | Molded PVC insulation between sockets and case                                  |
| Circuit Wiring Material         | Industrial grade copper bar welded (L, N, G)                                    |
| Product Size (L x W x D)        | 369.0 x 44.4 x 54.0 mm                                                          |
| Shipping dimensions (L x W x D) | 460.0 x 100.0 x 70.0 mm                                                         |
| Weight                          | 841 g                                                                           |

#### Environmental

|                                         |                              |
|-----------------------------------------|------------------------------|
| Maximum elevation (above MSL) Operating | 15,000 ft (4,500 m)          |
| Maximum elevation (above MSL) Storage   | 50,000 ft (15,000 m)         |
| Temperature Operating                   | -5 to 50° C (23 to 122° F)   |
| Temperature Storage                     | -25 to 80° C (-13 to 176° F) |
| Humidity Operating                      | 5 – 95% RH non-condensing    |
| Humidity Storage                        | 5 – 95% RH non-condensing    |

#### Compliance

|                          |                                                                                                                       |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Safety verification      | CE, LVD, EMC, FCC, VDE, EN 55032 : 2015, EN 55035 : 2017, EN 61000-2-11 : 2000<br>EN 61000-3-12 : 2007, TIS 2432-2555 |
| Environment verification | RoHS                                                                                                                  |
| Factory verification     | ISO9001, ISO14001, ISO45001                                                                                           |

### C-PDU [4] TIS outlet, Surge Protection, Illuminated Master Switch & Overload Protection with LED power indicator, TIS 16A Plug, Cable 3m with 1.5 sq.mm.

