

POWER DISTRIBUTION UNIT - PXB5PVFNB-C320C904-H

B-PDU [20] IEC320 C13, [4] IEC320 C19 outlet, 2 x Hydraulic Breaker 16A with LED power indicator, IEC309 32A Plug (2P + E), Cable 3m with 6 sq.mm.

Electrical

Input connector	1 x IEC309 32A Plug (2P+E)
Output connectors	20 x IEC320 C13 10A, 4 x IEC320 C19 Outlet
Nominal input voltage	200~250 VAC
No. of phases	1 phase
Acceptable input voltage	± 10% of normal voltage
Input frequency	50/60 Hz
Max. Power	8,000 W
Length of connection cable	3m x 6 sq.mm.

Physical

Power Input	Left end single input
Bracket Installation	2 Way Interchangeable L mounting brackets (2 directions)
Rack Installation	Vertical Mouting in Rack 19"
Control Function	2 x Hydraulic Breaker 16A with Plastic cover
Protection Function	2 x Hydraulic Breaker 16A with LED power indicator
Case Material	Aluminum Alloy (black)
Outlets Material	PC-ABS (black)
Insulation	Molded PVC insulation between sockets and case
Circuit Wiring Material	Industrial grade copper bar welded (L, N, G)
Product Size (L x W x D)	1178.0 x 44.4 x 90.0 mm
Shipping dimensions (L x W x D)	N/A
Weight	N/A

Environmental

Maximum elevation (above MSL) Operating	15,000 ft (4,500 m)
Maximum elevation (above MSL) Storage	50,000 ft (15,000 m)
Temperature Operating	-5 to 50° C (23 to 122° F)
Temperature Storage	-25 to 80° C (-13 to 176° F)
Humidity Operating	5 – 95% RH non-condensing
Humidity Storage	5 – 95% RH non-condensing

Compliance

Safety verification	CE, LVD, EMC, FCC, VDE, EN 55032 : 2015, EN 55035 : 2017, EN 61000-2-11 : 2000 EN 61000-3-12 : 2007
Environment verification	RoHS
Factory verification	ISO9001, ISO14001, ISO45001

POWER DISTRIBUTION UNIT - PXB5PVFNB-C320C904-H

B-PDU [20] IEC320 C13, [4] IEC320 C19 outlet, 2 x Hydraulic Breaker 16A with LED power indicator, IEC309 32A Plug (2P + E), Cable 3m with 6 sq.mm.

