

POWER DISTRIBUTION UNIT - PXB5PVFNB-C320C904

B-PDU [20] IEC320 C13, [4] IEC320 C19 outlet, Master Circuit Breaker 32A with LED power indicator, IEC309 32A Plug (2P + E), Cable 3m with 6 sq.mm.

Electrical	
Input connector	1 x IEC309 32A Plug (2P+E)
Output connectors	20 x IEC320 C13 10A Locking, 4 x IEC320 C19 Outlet
Nominal input voltage	200~250 VAC
No. of phases	1 phase
Acceptable input voltage	± 10% of normal voltage
Input frequency	50/60 Hz
Max. Power	8,000 W
Length of connection cable	3m x 6 sq.mm.

Physical	
Power Input	Left end single input
Bracket Installation	2 Way Interchangeable L mounting brackets (2 directions)
Rack Installation	Vertical Mounting in Rack 19"
Control Function	Legrand Master Circuit Breaker 32A with Plastic cover
Protection Function	Legrand Master Circuit Breaker 32A with LED power indicator
Case Material	Aluminum Alloy (black)
Outlets Material	PC-ABS (black)
Insulation	Molded PVC insulation between sockets and case
Circuit Wiring Material	Industrial grade copper bar welded (L, N, G)
Product Size (L x W x D)	1178.0 x 44.4 x 90.0 mm
Shipping dimensions (L x W x D)	N/A
Weight	N/A

Environmental	
Maximum elevation (above MSL) Operating	15,000 ft (4,500 m)
Maximum elevation (above MSL) Storage	50,000 ft (15,000 m)
Temperature Operating	-5 to 50° C (23 to 122° F)
Temperature Storage	-25 to 80° C (-13 to 176° F)
Humidity Operating	5 – 95% RH non-condensing
Humidity Storage	5 – 95% RH non-condensing

Compliance	
Safety verification	CE, LVD, EMC, FCC, VDE, EN 55032 : 2015, EN 55035 : 2017, EN 61000-2-11 : 2000 EN 61000-3-12 : 2007
Environment verification	RoHS
Factory verification	ISO9001, ISO14001, ISO45001

POWER DISTRIBUTION UNIT - PXB5PVFNB-C320C904

B-PDU [20] IEC320 C13, [4] IEC320 C19 outlet, Master Circuit Breaker 32A with LED power indicator, IEC309 32A Plug (2P + E), Cable 3m with 6 sq.mm.

